




DIMENSION TABLE (MODEL WITH BRAKE)

| MODEL                    | LL    | LR | LS | LW | LV | TP        | S  | RH |
|--------------------------|-------|----|----|----|----|-----------|----|----|
| <b>IC800VMM30LBKSE25</b> | 235.3 | 79 | 73 | 63 | —  | M12XP1.75 | 35 | 30 |



SHAFT END DETAILS

| MOTOR CONNECTION |          |
|------------------|----------|
| PIN              | FUNCTION |
| A                | BRAKE    |
| B                | BRAKE    |
| C                | —        |
| D                | U PHASE  |
| E                | V PHASE  |
| F                | W PHASE  |
| G                | GND      |
| H                | —        |
| I                | —        |

| ENCODER CONNECTION |           |     |          |
|--------------------|-----------|-----|----------|
| PIN                | FUNCTION  | PIN | FUNCTION |
|                    | 2500ppr   |     | 2500ppr  |
| A                  | A         | K   | —        |
| B                  | $\bar{A}$ | L   | SHIELD   |
| C                  | B         | M   | —        |
| D                  | $\bar{B}$ | N   | —        |
| E                  | —         | P   | —        |
| F                  | Z         | R   | GND      |
| G                  | $\bar{Z}$ | S   | DC+5V    |
| H                  | —         | T   | —        |
| J                  | —         |     |          |